

## Electromagnetic metering pumps

Electromagnetic metering pumps  
with precise flow monitoring, feedback & control



Conventional electromagnetic metering pumps generally suffer from low resistance to exposure of external liquids.

With improved sealing of not only the control unit but also the pump unit, a remarkable improvement to this exposure has been achieved in the EWN series.

# Electromagnetic metering pumps with precise flow monitoring, feedback & control



The EWN-Y electromagnetic pump combined with EFS flow sensor (option) provides accurate real time control & display of dosing rate.

The required flow rate is simply input to the pump. Through feedback from the EFS sensor, the pump constantly adjusts its speed to maintain the set dosing rate - even under changing temperature, viscosity, or suction & discharge pressure conditions.

The EFS is mounted directly on the pump to digitally display dosing rate per minute or hour - ALL WITHOUT ANY CALIBRATION.

The EWN-Y gives a proportional 4-20mA output signal of dosing rate and displays operating history such as total flow volume and power-on time.



EWN-Y  
With EFS flow sensor (option)

### Displaying flow rate

Pump flow rate may be displayed. In case the EFS flow sensor (option) is installed, the EWN-Y pump can display accurate real time flow rate without any calibration.

### Feedback control (with EFS)

Flow rate monitoring of individual strokes by the EFS sensor enable fast response feed back control. The feedback control maintains the set capacity by manually or externally with analog input signal.

### Discharge detection

Direct connection to the IWAKI FCP or FCM flow counter (excluding certain low- pressure models) allows effective monitoring of pump discharge (number of shots). Gas lock, abnormal pressure (only with FCP), etc., are also detectable.

### Alarm output and analog output functions are provided as standard function

Two types of alarm outputs and analog output are provided as standard functions. The analog output can be used for flow rate monitoring.

### Waterproof structure (IP65)

With the aim of improving resistance to exposure to liquid, the controller unit is installed on the back of the pump and the control panel is protected with a cover as standard equipment.

A rubber gasket is provided between the pump head and the bracket to prevent water from entering from the periphery of the pump head.


### Multi hose connection

The use of a new hose stopper eliminates a twist in tube connection.



# Technical data

## Construction



## Wet-end materials

	Pump head	Valve	Valve seat	O-ring	Diaphragm	Gasket
VC	PVC	Alumina ceramic	FKM	FKM	PTFE+EPDM (EPDM of Diaphragm is not wet-end.)	PTFE
VH		Hastelloy C276	EPDM	EPDM		
PC	GFRPP	Alumina ceramic	FKM	FKM		
PH		Hastelloy C276	EPDM	EPDM		
FC	PVDF	Alumina ceramic	PCTFE	-		
TC			FKM	FKM		
SH	SUS316	Hastelloy C276	SUS316	-		

## Pump identification

**EWN - B 11 VC □ E Y □**

- Series symbol**  
EWN series
- Diaphragm diameter**  
Effective diaphragm dia.  
09: 8mm 11: 10mm 16: 15mm  
21: 20mm 31: 30mm 36: 35mm
- Drive unit symbol**  
Average power consumption  
B: 20W C: 24W
- Wet-end material symbol**  
For details, see the table of materials.
- Connection**  
Blank: Ø4 x Ø6 (B09,B11,B16,B21,C16,C21)  
Ø9 x Ø12 (B31,C31,C36)  
For other option, please contact us.
- Controller function code**  
Y: Y type
- Power code**  
E: With European cord  
A: With Australian cord
- Special version code**  
C: High compression type  
H: High pressure type  
V: Viscosity type

## Specifications of pump

Model		B11	B16	B21	B31	C16	C21	C31	C36	
									VC/VH/PC/PH	FC/SH/TC
Capacity	L/hr	2.3	3.9	6.0	12.0	4.8	7.8	16.2	25.2	24.6
	mL/min	38	65	100	200	80	130	270	420	410
	mL/shot	0.05 to 0.1	0.09 to 0.18	0.14 to 0.28	0.28 to 0.56	0.09 to 0.22	0.14 to 0.36	0.3 to 0.75	0.47 to 1.17	0.46 to 1.14
Rated discharge pressure	MPa	1.0	0.7	0.4	0.2	1.0	0.7	0.35	0.2	0.2
Max. pressure	MPa	(1.4)	(0.8)	(0.5)	-	(1.2)	(0.8)	-	-	-
Stroke rate	% (spm)	0.1 to 100 (1 to 360)								
Stroke length range	% (mm)	50 to 100 (0.5 to 1.0)				40 to 100 (0.5 to 1.25)				
Current	A	0.8				1.2				
Average power consumption	W	20				24				

• Each discharge capacity shown above is at discharge pressure (stroke length 100%, stroke rate 100%) and increases as a discharge pressure reduces.

• The performance is based on pumping clean water at ambient temperature at rated voltage.

• Liquid temperature -VC/VH types: -10 to 40°C -PC/PH/FC/SH/TC types: -10 to 60°C

• Max pressure is not guaranteed under any discharge condition. Max pressure of PVC type is 1.2MPa. Please contact us for details.

## Specifications of controller

Model			EWN-Y	With EFS	Without EFS	
Operational mode	MAN control		MAN(Manual)	•	•	0.1-100.0%(1-360spm)
			Feedback control	•	N/A	0.1 - 999.9mL/min 0.001 - 59.994 L/H 0.001 - 15.829 GPH
	EXT control		DIV	N/A	•	/1-9999
			MULT	N/A	•	x1-9999
			Analog rigid	•	•	4-20, 20-4, 0-20, 20-0mA proportional control to stroke rates
			Analog variable	•	•	2 - point setting (Analog variable) (Proportional control to flow/stroke rates in the range of 0-20mA)
			BATCH	•	N/A	0.1 - 99999.9 mL 0.001 - 99.999 L 0.001 - 26.385 G
Display	LCD		14seg-5digits backlit LCD Operating conditions and Flow rates etc			
	LED	ON	A 2-color LED lights in orange when turning on power and in green during operation.			
		STOP	A 2-color LED lights in red when receiving the STOP signal and in orange when receiving the PreSTOP signal.			
		OUT	A LED lights in red when the pump is transmitting a signal to external devices.			
Keypad	5keys		START/STOP, EXT, ▲(UP), ▼(DOWN), Disp			
Control function	STOP/Pre-STOP		Pump keeps running when Pre-STOP is activated.Pump stops when STOP is activated.			
	Prime		Pump runs at max. stroke rate while up and down keys are pushed.			
	Key lock		Key can be locked and unlocked.			
	Inter lock		Operation stop at contact input* <sup>1</sup>			
	Reading calibration		Reading adjustment of flow volume per shot			
	Buffer		ON/OFF of the batch control buffer memory			
Input	Pulse signal input for batch control		No voltage contact or open collector* <sup>2</sup>			
	Analogue		0-20mADC (Input resistance is 220Ω.)			
	STOP/Pre-STOP (Level sensor)		No voltage contact or open collector* <sup>2</sup>			
	AUX		No voltage contact or open collector* <sup>2</sup>			
	Interlock		No voltage contact or open collector* <sup>2</sup>			
	Batch		No voltage contact or open collector* <sup>2</sup>			
Output	OUT1		No voltage contact (Mechanical relay), 250VAC 3A (Resistive load) Either the Signal recognition output* <sup>3</sup> , Control error, or Poor flow detection is selectable (default: STOP).			
	OUT2		No voltage contact (PhotoMOS relay), AC/DC24V 0.1A Either the Sensor signal output, Synchronous output, Signal recognition output* <sup>3</sup> , Control error or Poor flow detection is selectable.			
	Analogue		4-20mA DC (Allowable load resistance : 500Ω)			
Data logging			Total flow volume Total number of strokes (1=1000 shots) Total number of signal outputs (OUT1) Total number of signal outputs (OUT2) Total power connection time Total operating time			
Buffer memory			Nonvolatile memory			
Power voltage**			100-240VAC 50/60Hz			

Note 1: The setting can be changed to "operation resumption at contact input".

Note 2: The maximum applied voltage from the pump to an external contact is 12V at 2.3mA. When using a mechanical relay, its minimum application load should be 1mA or below.

Note 3: STOP/ Pre-STOP/ Interlock/ Batch completion outputs are separately enabled.

Note 4: Observe the specified power voltage range. Otherwise failure may result. The allowable power voltage range is 90-264VAC



# Optional accessories

## Sensors


### · EFS flow sensor

The EFS flow sensor is an electromagnetic flow sensor for the electromagnetic metering pump, EWN-Y series. The flow sensor can measure the volume per stroke of pulsating output without the assistance of pulsation dampers.



#### · Constructions and materials


	FT	FH
O ring	FKM	EPDM
Body	PVDF	
Electrode	Titanium	Hastelloy C22 or equivalent




#### · Specifications

Applicable pump	EWN-B11, B16, B21, C16 - Y
Accuracy	More than 40mL/min 5% RD Less than 40mL/min 2mL/min
Available medium	Minimum conductivity 10ms/cm
Liquid temp.	0 to 60 °C

#### · Identification



#### · Dimensions in mm




### · FCP flow counter (Posi-flow)

The FCP flow counter (Posi-flow) detects the pump pulsation by a pressure sensor. This sensor can check not only the number of dosing but also abnormal pressure (Low and high) as pipe clogging, gas-lock or pipe leakage.



#### · Constructions and materials


	1PC	1PE	1VC	1VE
O ring	FKM	EPDM	FKM	EPDM
Body	GFRPP		PVC	
Sensor	Ceramic (Al <sub>2</sub> O <sub>3</sub> ) 99.7%			




### · Specifications

Applicable pump	EWN-B11, B16, B21, C16, C21
Operating pressure range	0.30 to 1.0 MPa
Indicators	Stop / Error : LED disappears Pressure error : LED lights redly Normal operation : LED lights greenly
Liquid temp.	0 to 40 °C

#### · Identification



#### · Dimensions in mm




### · FCM flow checker

The FCM is a simple flow checker for the electromagnetic metering pump. A magnet molded float sensor and proximity switch detects pulsation of dosing output.



#### · Constructions and materials


	VC	VH
Body	PVC	
Float	PVC	
Plate	PVC	
O ring	FKM	EPDM



#### · Specifications

Power voltage	5-24VDC
Max consumption current	8 mA
Max load capacity	15 mA
Output	NPN Open collector
Frequency	Max 6 Hz
Pulse output range	Min flow rate: 0.1 mL/shot Min discharge pressure: 0.2 MPa Max discharge pressure depends on each pump spec. Pump stroke rate: 1-360 spm Pump stroke length: Fixed to 100% (Factory setting)

#### · Identification



## Accessories

### • Check valve CAN / CBN / CS

This has the function of a non-return valve and prevents siphon and overfeed.

**CAN:** Available in PVC and GFRPP.

**CBN:** In-line type to be connected in the middle of a hose; made of PVC.

**CS:** Made of stainless steel for SH type.



#### • Specifications

Model	Connection		Set pressure MPa	Material			Applicable pump
	Inlet mm	Outlet mm		Body	Spring	O-ring	
<b>CAN-1VC (1V)</b>	4x6, 5x8	R3/8 and R1/2	0.17±0.04	PVC (GFRPP/CFRPP)	Hastelloy C276	FKM	EWN-B09, 11, 16, 21, C16, 21
<b>CAN-1VE (1E)</b>	6x8, 6x12					EPDM	
<b>CAN-1VC-H (1E)</b>	4x9, 4x6					FKM	
<b>CAN-1VE-H(1E)</b>	6x8, 1/4"x3/8"					EPDM	EWN-C31
<b>CAN-2VC (2V)</b>	6x12, 9x12					FKM	
<b>CAN-2VE (2E)</b>	6x12, 9x12	0.05 ± 0.04 - 0.03	0.17±0.04	PVC	Hastelloy C276	EPDM	
<b>CAN-2VCL (2VL)</b>	6x12, 9x12					FKM	EWN-B31, C36
<b>CAN-2VEL (2EL)</b>	6x12, 9x12					EPDM	
<b>CBN-1VC</b>	4x6, 5x8	6x8, 6x12	0.17±0.04	PVC	Hastelloy C276	FKM	EWN-B09, 11, 16, 21, C16, 21
<b>CBN-1VE</b>	6x8, 6x12					EPDM	
<b>CS-1S</b>	Rc1/4	Rc1/4	0.2±0.03	SUS316	Hastelloy C276	-	EWN-B11, 16, 21, C16, 21, 31
<b>CS-1SL</b>			0.05±0.03				

### • Siphon preventing valve BVC

Made of PVC or GFRPP consisting of non-metallic parts.



#### • Specifications

Model	Connection		Set pressure MPa	Material		Applicable pump
	Inlet mm	Outlet mm		Body	O-ring	
Note <b>BVC-1</b> □□	4x6, 9x12	R3/8 or R1/2	0.2 or 0.05	PVC	FKM or EPDM	All models

Note: Different models are available. Please contact for particulars.

### • Multi-function valve MFV

This valve has the multi-function of air vent, pressure release inside pipe, pressure relief and back pressure valve.



#### • Specifications

Model	Tube connection	Set pressure		Material	Applicable pump
		Back pressure valve	Relief valve		
<b>MFV-HTC</b>	4x6mm, 5x8mm, 6x8mm, 6x12mm, 9x12mm, 10x12mm, 1/4x3/8, 3/8x1/2	0.25±0.1 MPa	1.25±0.2 MPa	PVDF / FEPM / PTFE+EPDM* *(Not a wet end)	EWN-B11, 16, 21, C16, 21, 31, 36
<b>MFV-MTC</b>		0.25±0.1 MPa	0.55±0.1 MPa		
<b>MFV-LTC</b>		0.1±0.05 MPa	—		

### • Foot valve FS / FSP / FSTC

This foot valve with a strainer is made of PVC or GFRPP.



#### • Specifications

Model	Tube connection	Material	Applicable pump
<b>FSV</b>	4x6mm	PVC / FKM / Alumina ceramic	All models
<b>FSE</b>	5x8mm	PVC / EPDM / HastelloyC276	
<b>FSPV</b>	6x8mm	GFRPP / FKM / Alumina ceramic	
<b>FSPE</b>	6x12mm	GFRPP / EPDM / HastelloyC276	
<b>FSPE</b>	9x12mm	GFRPP / EPDM / HastelloyC276	
<b>FSTC</b>	10x12mm	PVDF / FKM / Alumina ceramic	

### • Chemical tank EXDT

This is a polyethylene round tank.



**Capacity:** 35, 60, 100, 200 or 300L

### • Priming set PS

Made of PVC furnished with level sensor(s) and foot valve.



#### • Specifications

Model	Level switch	Connection mm	Length mm
<b>PS-1</b>	Single	4x6, 5x8, 6x8, 6x12, 9x12	520, 650, 810, 1000, 1350
<b>PS-2</b>	Double		520, 720, 810, 1000, 1350







### • Pulse oscillating flow meter



#### • Specifications

Connection	Max. capacity	Range of pulse
3/4"	5m³/h	1xOutput pulse against 0.25L
		1xOutput pulse against 0.50L
		1xOutput pulse against 1.00L
1"	12m³/h	1xOutput pulse against 0.25L
		1xOutput pulse against 0.50L
		1xOutput pulse against 1.00L
1 1/2"	20m³/h	1xOutput pulse against 0.25L
		1xOutput pulse against 0.50L
		1xOutput pulse against 1.00L

## Dimensions in mm



[www.iwakipumps.jp](http://www.iwakipumps.jp)

IWAKI CO.,LTD. 6-6 Kanda-Sudacho 2-chome Chiyoda-ku Tokyo 101-8558 Japan TEL : (81)3 3254 2935 FAX : 3 3252 9829

### EUROPE / U.S.A.

European office : IWAKI Europe GmbH  
 Holland : IWAKI Europe (NL Branch)  
 Belgium : IWAKI Belgium N.V.  
 Denmark : IWAKI Nordic A/S  
 Finland : IWAKI Suomi Oy  
 France : IWAKI France S.A.  
 Germany : IWAKI Europe GmbH  
 Italy : IWAKI Italia S.R.L.  
 Norway : IWAKI Norge AS  
 Spain : IWAKI Iberica Pumps, S.A.  
 Sweden : IWAKI Sverige AB  
 Switzerland : IWAKI (Schweiz) AG  
 U.K. : IWAKI Pumps (UK) Ltd.  
 U.S.A. : IWAKI America Inc.  
 Argentina : IWAKI America Inc. (Argentina Branch)

TEL: (49)2154 9254 0 FAX: 2154 9254 48  
 TEL: (31)547 293 160 FAX: 547 292 332  
 TEL: (32)13 67 02 00 FAX: 13 67 20 30  
 TEL: (45)48 24 2345 FAX: 48 24 2346  
 TEL: (358)9 2745810 FAX: 9 2742715  
 TEL: (33)1 69 63 33 70 FAX: 1 64 49 92 73  
 TEL: (49)2154 9254 50 FAX: 2154 9254 55  
 TEL: (39)0444 371115 FAX: 0444 335350  
 TEL: (47)66 81 16 60 FAX: 66 81 16 61  
 TEL: (34)943 630030 FAX: 943 628799  
 TEL: (46)8 511 72900 FAX: 8 511 72922  
 TEL: (41)26 674 93 00 FAX: 26 674 93 02  
 TEL: (44)1743 231363 FAX: 1743 366507  
 TEL: (1)508 429 1440 FAX: 508 429 1386  
 TEL: (54)11 4745 4116

### ASIA / OCEANIA

Australia : IWAKI Pumps Australia Pty Ltd.  
 China : IWAKI Pumps Co., Ltd.  
 Hong Kong : IWAKI Pumps (Shanghai) Co., Ltd.  
 Shanghai : GFTZ IWAKI Engineering & Trading Co., Ltd.  
 Guangzhou : GFTZ IWAKI Engineering & Trading Co., Ltd. (Beijing office)  
 Beijing : IWAKI Korea Co., Ltd.  
 Korea : IWAKI Sdn. Bhd.  
 Malaysia : IWAKI Singapore Pte Ltd.  
 Singapore : IWAKI Singapore (Indonesia Branch)  
 Indonesia : IWAKI Pumps Taiwan Co., Ltd.  
 Taiwan : IWAKI (Thailand) Co., Ltd.  
 Thailand : IWAKI Pumps Vietnam Co., Ltd.  
 Vietnam : IWAKI Pumps Vietnam Co., Ltd.

TEL: (61)2 9899 2411 FAX: 2 9899 2421  
 TEL: (852)2607 1168 FAX: 2607 1000  
 TEL: (86)21 6272 7502 FAX: 21 6272 6929  
 TEL: (86)20 8435 0603 FAX: 20 8435 9181  
 TEL: (86)10 6442 7713 FAX: 10 6442 7712  
 TEL: (82)2 2630 4800 FAX: 2 2630 4801  
 TEL: (60)3 7803 8807 FAX: 3 7803 4800  
 TEL: (65)6316 2028 FAX: 6316 3221  
 TEL: (62)21 6906606 FAX: 21 6906612  
 TEL: (886)2 8227 6900 FAX: 2 8227 6818  
 TEL: (66)2 322 2471 FAX: 2 322 2477  
 TEL: (84)613 933456 FAX: 613 933399



**Caution for safety use:** Before use of pump, read instruction manual carefully to use the product correctly.  
 Actual pumps may differ from the photos. Specifications and dimensions are subject to change without prior notice. For further details please contact us.

**Legal attention related to export.**  
 Our products and/or parts of products fall in the category of goods contained in control list of international regime for export control.  
 Please be reminded that export license could be required when products are exported due to export control regulations of countries.